



REVISION RECORD			
REV.	CONTENT	MOD.	DATE
△	初版发行		

NOTES:  
 Pitch : 2.5mm  
 Rated Voltage : 150 V  
 Rated Current : 4A  
 Withstand Voltage :  
 AC2000V for 1 minute  
 Insulation Resistance :  
 5MΩ / DC500V  
 Using Temperature Range :  
 -40℃ ~ +105℃  
 Wire range :24 ~20 AWG  
 Stripping length : 10mm

技术要求:  
 间距: 2.5mm  
 额定电压: 150V  
 额定电流: 4A  
 耐电压值: AC2000V/min  
 绝缘阻抗: 5MΩ/DC500V  
 使用条件: -40℃~+105℃  
 适用线规: 24~20 AWG  
 剥线长度: 10mm

	pitch dimension			Nominal dimension					— ▱ ⌒
	over 0 to 6	over 6 to 10	over 10 to 24	over 0 to 30	over 30 to 60	over 60 to 100	over 100 to 150	over 150	
variable range									
Tolerance	±0.1	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10

5	LC6-2.5-弹片	F2A0DLC625BV	P	不锈钢	
4	LC6-2.5-夹子	1023B0001AV	P	黄铜	镀镍
3	LC6-2.5-按钮	1023D0YXXAV	P	PA66	
2	LC6-2.5-盖板	1023C0YXXAV	1	PA66	
1	LC6-2.5-主体	1023A0YXXAV	1	PA66	
NO.	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
DES.	ARRIB	DATE	12-02-23	UNITS	mm
CHK.		DATE		SIZE	A4
APP.		DATE		SCALE	1:1
				DWG NO.	SP-2-1023001
				REV:	V0
上海联捷电气有限公司 Shanghai Elinker Electric CO., LTD				TITLE	LC6-2.5-XXP-1Y-00A LC6-2.5-成品