

REVISION		RECORD	
REV.	CONTENT	MOD.	DATE
△	初版发行		

NOTES:  
Pitch : 5.08mm  
Rated Voltage : 300V  
Rated Current : 15A  
Withstand Voltage :  
AC2500V for 1 minute  
Insulation Resistance :  
500MΩ / DC500V  
Using Temperature Range :  
- 40℃ ~ + 105℃

技术要求:  
间距: 5.08mm  
额定电压: 300V  
额定电流: 15A  
耐电压值: AC2500V/min  
绝缘阻抗: 500MΩ/DC500V  
使用条件: -40℃ ~+105℃

10	ZBD5-XXP标记号	ZBD5-XXP	1	PA66-V0			
9			1				
8							
7	LD1-2.5-弹片	6LD1B0001AV	2P	SUS301			
6	LD1-2.5-导电件	6LD1B0002AV	P	紫铜	镀雾锡		
5	LD1-2.5-按钮	6LD1A400204V	2P	PBT	橘黄		
4	LD1-2.5-XX壳体	6LD1C400203V	1	PA66-V0	绿色		
3	LD1-2.5-主体	6LD1A400203V	1	PA66-V0	绿色		
2	LZ3H-5.08-直针	1031B0002AV	P	黄铜	镀雾锡		
1			1	PA66			
NO.	NAME OF PART	NO. OF PART	Q' TY	MATERIAL	NOTES		
DES.	ZJL	DATE	2022/8/3	UNITS	MM	THIRD ANGLE PROJECTION	SHEET
CHK.		DATE		SIZE	A4		1 of 1
APP.		DATE		SCALE	1:1	DWG. NO.	SP-1153A01
<b>上海联捷电气有限公司</b> Shanghai Elinker Electric CO.,LTD						TITLE	LD70K-5.08-XXP-1Y-00A LD70K-5.08-成品

	Nominal dimension					— 
	over 0 to 30	over 30 to 60	over 60 to 100	over 100 t		
variable range						
Tolerance	±0.2	±0.3	±0.5	±0.7		0.05/10