



REVISION RECORD			
REV.	CONTENT	MOD.	DATE
△	初版发行		

NOTES1:
 UL Standard:
 1.Voltage Rating: 300V, Current Rating: 8A
 2.Suitable Electric Wire: 28-16AWG
 IEC Standard:
 1.Voltage Rating: 160V, Current Rating: 8A
 2.Suitable Electric Wire: 26-14AWG

NOTES2:
 1.Pitch: 3.81mm
 2.Withstand Voltage: AC2500V for 1 minute
 3.Insulation Resistance: 500MΩ / DC500V
 4.Using Temperature Range: -40℃ ~ +105℃

技术要求1: 技术要求2:
 UL 标准: 1.间距: 3.81mm
 1.额定电压: 300V, 额定电流: 8A 2.耐压值: AC2500V/min
 2.适用线规: 28~16AWG 3.绝缘阻抗: 500MΩ/DC500V
 IEC 标准: 4.使用条件: -40℃~+105℃
 1.额定电压: 160V, 额定电流: 8A
 2.适用线规: 26~14AWG

7	LZ1HM-7.62耳朵螺母	SM00B300000V	2	黄铜	
6	LZ1-5.08-螺母	SM00B250000V	2	黄铜	
5	LC60-3.81五金件	2079B0001AV	P	磷青铜	镀亮锡
4	LC6-3.81-弹片	F2A0DLC638BV	P	不锈钢	
3	LC6-3.81-按钮	1043D0YXXAV	P	POM	
2	LC60MGC1-3.81-盖板	2096C0YXXAV	1	PA66-V0	
1	LC60-3.81-本体	1043A0YXXAV	1	PA66-V0	
NO.	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
DES.	WYY	DATE	23/11/10	UNITS	MM
CHK.		DATE		SIZE	A4
APP.		DATE		SCALE	1:1
				DWG NO.	SP-1-2082140
				REV:	V0
 上海联捷电气有限公司 Shanghai Elinker Electric Co., LTD				TITLE	
				LC60MGC1-3.81-XXP-17-00A (XXP表示几位, 17表示任意颜色) LC60MGC1-3.81-成品	

	pitch dimension			Nominal dimension					— ◇ ⌒
	over	over	over	over	over	over	over	over	
variable range	0	6	10	0	30	60	100	150	
	to	to	to	to	to	to	to	to	
	6	10	24	30	60	100	150		
Tolerance	±0.1	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	0.05/10